

BOLLARD MOUNT GUIDE

LPL12/PL12 and LBD-H/BD-H Series Bollard Mount Options



BD-1/2 Universal 1/2" Male Adapter (120V or 12V)
The 1/2" mount does not come with a stake and is intended for mounting to 1/2" NPS threaded electrical devices.



BD-G/S2 Ground Stake (12V)
The G/S2 2" diameter stake stabilizes BD-H series bollards or PL12 path lights up to 30" high. This mount is designed for ground installations and can accommodate up to one 3/4" or three 1/2" conduits.



BD-G/S2.5 Ground Stake (12V)
The G/S2.5 2 1/2" diameter stake stabilizes BD-H series bollards or PL12 path lights up to 30" high. This mount is designed for ground installations and can accommodate up to three 3/4" or four 1/2" conduits.



BD-T/R-12 Trident Spike (12V)
The Trident Spike stabilizes luminaires when mounted in loose soil with its 4x1/4" thick mount plate. Available in a 12" spike length the Trident Spike is constructed entirely from stainless steel.



BD-L/P Leveling Pedestal (120V or 12V)
The Leveling Pedestal is a perfect solution for installing onto a concrete footing. Equipped with three adjustable leveling feet this mount corrects uneven surfaces up to 6° off horizontal. This mount is designed to fit over up to three 3/4" bundled PVC conduits.



BD-S/M Surface Mount (120V or 12V)
Machined from solid brass the Surface Mount is equipped with stainless steel hardware and a nonobtrusive spun copper escutcheon to hide mount screws. For durable installations of up to 30" high bollards mounted to solid, level surfaces only. Designed to fit over up to three 3/4" bundled PVC conduits.



BD-P/M Pedestal Mount (120V or 12V)
The P/M is a robust, solid brass mount system designed to be cast into concrete to create a durable, unmovable mount point for high end residential or commercial projects using 12V or 120V. Toolless entry.



BD-JB3 Burial J-box (120V or 12V)
The JB3 provides a solid machined brass wiring box with 2 1/2" conduit entries on the bottom. Add "S" for PVC stabilizing stake or "T/R" for 12" Stainless Steel Strident Spike. Toolless entry.

BD250 Series Bollard Mount Options



BD250-1/2 Universal 1/2" Male Adapter (120V or 12V)
The 1/2" mount does not come with a stake and is intended for mounting to 1/2" NPS threaded electrical devices.



BD250-G/S Ground Stake (12V)
The ground stake, stabilizes our larger scale path lights and our 250 series line of bollards. To be used for ground installations with remote transformer.



BD250-T/R-12" Trident Spike (12V)
The Trident Spike stabilizes luminaires when mounted in loose soil with its 4x1/4" thick mount plate. Available in a 12" spike length the Trident Spike is constructed entirely from stainless steel.



BD250-L/P Leveling Pedestal (120V or 12V)
The Leveling Pedestal is a perfect solution for installing onto a concrete footing. Equipped with three adjustable leveling feet this mount corrects uneven surfaces up to 6° off horizontal. This mount is designed to fit over up to three 3/4" bundled PVC conduits.



BD250-S/M Surface Mount (120V or 12V)
Machined from solid brass the Surface Mount is equipped with stainless steel hardware and a nonobtrusive spun copper escutcheon to hide mount screws. For durable installations of up to 30" high bollards mounted to solid, level surfaces only. Designed to fit over up to three 3/4" bundled PVC conduits.



BD250-P/M Pedestal Mount (120V or 12V)
The P/M is a robust, solid brass mount system designed to be cast into concrete to create a durable, unmovable mount point for high end residential or commercial projects using 12V or 120V. Can be specified with a 60W 120V to 12V transformer or 20W/39W electronic Metal Halide ballast; toolless entry.



BD250-JB3 Burial J-Box (120V or 12V)
The JB3 provides a solid machined brass wiring box with 2 1/2" conduit entries on the bottom. Add "S" for PVC stabilizing stake or "T/R" for 12" Stainless Steel Strident Spike.



BD250-P/B Power Box (120V to 12V)
The Power Box transformer enclosure provides for 120 volt line voltage feed to our low voltage luminaires and 250 series bollards. The Power Box is equipped with a 60W electronic transformer. J-box accommodates up to 2, 1/2" conduits. Add "S" for PVC stabilizing stake or "T/R" for 12" Stainless Steel Strident Spike.

BD350 Series Bollard Mount Options



BD350-1/2 Universal 1/2" Male Adapter (120V or 12V)
The 1/2" mount does not come with a stake and is intended for mounting to 1/2" NPS threaded electrical devices.



BD350-G/S Ground Stake (12V)
The ground stake, stabilizes our larger scale path lights and our 350 series line of bollards. To be used for ground installations with remote transformer.



BD350-T/R-12 Trident Spike (12V)
The Trident Spike stabilizes luminaires when mounted in loose soil with its 4x1/4" thick mount plate. Available in a 12" spike length the Trident Spike is constructed entirely from stainless steel.



BD350-L/P Leveling Pedestal (120V or 12V)
The Leveling Pedestal is a perfect solution for installing onto a concrete footing. Equipped with three adjustable leveling feet this mount corrects uneven surfaces up to 6° off horizontal. This mount is designed to fit over up to three 3/4" bundled PVC conduits.



BD350-S/M Surface Mount (120V or 12V)
Machined from solid brass the Surface Mount is equipped with stainless steel hardware and a nonobtrusive spun copper escutcheon to hide mount screws. For durable installations of up to 30" high bollards mounted to solid, level surfaces only. Designed to fit over up to three 3/4" bundled PVC conduits.




BD350-P/M Pedestal Mount (120V or 12V)
The P/M is a robust, solid brass mount system designed to be cast into concrete to create a durable, unmovable mount point for high end residential or commercial projects using 120V. Toolless entry.

BD400 Series Bollard Mount Options



BD400-L/P Heavy Duty Leveling Pedestal (120V)
The Leveling Pedestal is a perfect solution for installing onto a concrete footing. Equipped with three adjustable leveling feet this mount corrects uneven surfaces up to 6° off horizontal. This mount is designed to fit over up to three 3/4" bundled PVC conduits. Recommended for concrete installations.



BD400-S/M Heavy Duty Surface Mount (120V)
Machined from solid brass the Surface Mount is equipped with stainless steel hardware and a nonobtrusive spun copper escutcheon to hide mount screws. For durable installations of up to 48" high bollards mounted to solid, level surfaces only. Designed to fit over up to three 3/4" bundled PVC conduits.